


**FASTER  
CLEANER  
EASIER  
AFFORDABLE  
ENCAPSULATION**

NO POSTAGE  
NECESSARY  
IF MAILED  
IN THE  
UNITED STATES



**BUSINESS REPLY MAIL**

FIRST-CLASS MAIL PERMIT NO. 255 BROOKFIELD, WI

POSTAGE WILL BE PAID BY ADDRESSEE

**VOLATILE FREE INC**  
PO BOX 344  
BROOKFIELD WI 53008-9930



**VOLATILEFREE**INC

P.O. Box 344 · Brookfield, WI 53008

**New Approach  
for the Application  
of Hardcoats**



\* simulated application

**VFI-Qwik Spray System**



**VOLATILEFREE**INC

P.O. Box 344 · Brookfield, WI 53008  
(800) 307-9218 · (262) 787-0400 · fax (262) 787-0500  
[www.volatilefree.com](http://www.volatilefree.com)

**FASTER - CLEANER - EASIER - AFFORDABLE**

You can now encapsulate pre-sculpted EPS parts with a rigid polyurethane hardcoat without investing all the money for expensive machinery or incurring large labor costs associated with a multi-step, brushable hardcoat system. Our VFI-2538 high performance spray encapsulant comes supplied in cartridges, meaning your valuable time is not spent premixing material or involved in equipment clean-up since most parts are disposable.

The portability of our system will allow you to conveniently make on-site repairs, augment existing sculptures or even construct the sculpture on site, providing an easy solution for shipping cumbersome works of art.

**Gun Description:**

The VFI-Qwik Spray System is easier to operate than any spray system you are currently using or considering to purchase, so simple and easy that no special training is required. When you purchase the Qwik Spray System you are provided with the complete equipment package reducing the cost of special or extra equipment, (air supply not included).

**Product Description:**

VFI-2538 sprayable encapsulant is a 100% solids, two-component aromatic polyurethane coating, designed to provide an impact resistant shell for numerous different substrates including EPS, insulative foams and wood. This product is environmentally safe and contains no VOC's.

Results from a laboratory study indicated a ten-fold savings in labor costs by choosing the Qwik-Spray System over a slow cure brushable encapsulant for application over EPS. Due to the quicker cure speed, the application of VFI-2538 with the Qwik Spray System was finished the same day, while the multi-step, brushable work was completed over six days. The control of the application thickness also eliminated the need of removing drips and restoring detail prior to painting.



The VFI-2538 sprayable encapsulant is sold in cases of 6 kits. Each kit contains 1500 ml of material. A case will cover 127 square feet with 30 mls of coating. Included with each kit is a static mixer with an air atomizing tip.



**Call VFI at (800) 307-9218**  
**www.volatilefree.com**

**YES!** Tell me more about the VFI-2538 Qwik Spray Encapsulant.

Call me at this number: ( ) - - Best time to call AM PM

E-mail address: \_\_\_\_\_

Send more information:

Name \_\_\_\_\_  
 Title \_\_\_\_\_  
 Company \_\_\_\_\_  
 Address \_\_\_\_\_  
 City \_\_\_\_\_ State \_\_\_\_\_ Zip \_\_\_\_\_

This information and technical advice provided herein are believed to be reliable and accurate to the best knowledge of Volatile Free, Inc., as based on tests and should serve only as a recommendation. As the manufacturer, Volatile Free, Inc. makes no representations or warranties of any kind, expressed or implied, including but not limited to all implied warranties of merchantability or fitness for use or a particular purpose for the product. Volatile Free, Inc. makes no representations or warranties as to the results of the use of the product and assumes no obligation or liability in connection therewith. Volatile Free, Inc. is not liable for any incidental or consequential damages of any sort from use of this product. The information provided herein is subject to change at anytime without notice. Information changes may include, but are not limited to, commercial and technical changes, changes in pricing, physical characteristics and packaging.